

**G50R Rechargeable light with emergency light function**



Small, powerful LED spotlight combined with the Li-ion - Battery Technology.

Material cabinet	plastic shockproof fluorescent blue surface - luminescent in darkness.
Lamp head	aluminium black
Switching mode	5 LED: 100%/80%/50%/Flashing/Dimming 3 LED FLOOD: 100% 2 LED SPOT: 100%
Additional Features	Lamp head adjustable +90° / -30° Base with magnet 4x 50N
Charger	230VAC 50/60Hz IP20 Car-adapt. 12/24VDC IP20
Capacity display	LED2 GREEN >70% LED1 GREEN 40-70% LED ORANGE 10-40% LED RED <10%

**Technical data**

LED Power	5 x 3W
Luminous flux	900lm
Battery / Operating Voltage	Li-Ionen 4.400mAh / 7,4VDC
Lighting time	5 LED: 100% approx. 4h, 80% approx. 6h, 50% approx. 9h, Dimming 10% approx. 48h
	3 LED FLOOD: 100% 10h
	2 LED SPOT: 100% 12h
Charging time	approx. 4,5h
Luminous angle	Flood/Spot
Type of protection	IP66
Weight	approx. 1100g incl. Powerpack
Dimensions L x W x H	260 x 120 x 102 mm
Operating Temperature range	-20 °C to +45 °C
Charging temperature range	+10 °C to +30 °C



G50R		
EDP-No.	Product-ID-No.	Description
840171	G50R.ARBEITSLEUCHE.LI-ION.230VAC.12/24/230V	Portable light battery Li-Ion incl. charger 230VAC + charger 12 / 24VDC, incl. shoulder strap, with magnets, fluorescent, IP66.
840214	G50R.ARBEITSLEUCHE.LI-ION.230VAC.12/24/230V.G	Portable light battery Li-Ion incl. charger 230VAC + charger 12 / 24VDC, incl. shoulder strap, with magnets, fluorescent, IP66, incl. engraving.
840182	G50R.WANDMONTAGPLATTE.GVZ	Wall mounting plate for G50R

